

Replaces open tube	6 mm
Noise reduction	25 dB(A)
Air-/ cost savings	39 Nm³/h



Silvent 220W-Z	L=225mm
Silvent 230W-Z	L=325mm
Silvent 240W-Z	L=425mm
Silvent 250W-Z	L=525mm

Silvent 250 W-Z

Flexblow L= 500mm with nozzle SV 9002 W-Z | 5,5N - AG 1/4 male 250 W-Z

Silvent 250 W-Z: The Silvent 9002W-Z nozzle mounted on a bendable FlexBlow hose. Keeps desired position even at high pressure. Available in 4 different standard lengths. Compressed air is optimally used in this flat nozzle, which through its unique design introduces a completely new blowing technology feature. The aerodynamic nozzle design achieves the effect by maximizing entrainment of air. Each orifice is also uniquely designed to optimize the entrainment area. These small orifices combined with the aerodynamic slots of the nozzle provide high efficiency.

Technical data

Item number	753154
Weight	360 g
Air consumption	28 Nm³/h
Air connection	1/4 "
Blowing Power	5,5 N
Max. Operating pressure	1,0 MPa
Max temperature	70 °C
Noise	78 dB(A)
Material	Zinc
Air pattern	Flat
Connection	1/4 BSP