



**Product test possible!**

<b>Replaces open tube</b>	<b>25 mm</b>
<b>Noise reduction</b>	<b>85 %</b>
<b>Air-/ cost savings</b>	<b>18 %</b>

## Silvent 475L

### Double nozzle ring

SILVENT 475 L, with its double nozzle ring, is entirely unique. Two different blowing patterns unite to achieve maximum results. The outer ring provides initial cleaning and prepares the surfaces for the inner system, which then completes the drying or cleaning process. The system is designed to clean or dry cables, pipes, sections, hoses, etc. that require extra high blowing force or pass through the doughnut at high speed. Efficient and uniform 360° coverage is guaranteed - even at the opening in the doughnut, where extra powerful nozzles are mounted at the optimal blowing angle. SILVENT 475 L allows problem-free insertion and removal of material with diameters of 100 to 205 mm (4 - 8.1") through the opening in the doughnut. It features robust attachment lugs for easy and safe mounting. Fully complies with the noise limitations of the EU Machine Directive and OSHA safety standards. Patented."

### Technical data

Item number	746210
Air consumption	948 Nm <sup>3</sup> /h
Air connection	3/4 "
Sound	104 dB(A)
Blowing Power	148.9 N
Dimensions LxWxH	365 x 336 x 78 mm
Material	Zinc
Air pattern	Misc.